



**LAXMI**<sup>TM</sup>  
DRIP SYSTEMS



## लक्ष्मी उद्योग समुहातील उत्तम गुणवत्ता असलेली दर्जेदार उत्पादने.

- ❖ उत्तम गुणवत्ता असलेली ठिबक सिंचनासाठी लागणारे दर्जेदार रबर उत्पादने.
- ❖ ईनलाईन, ऑनलाईन लॅटरल, ड्रिप अॅसेसरीज.
- ❖ सर्व फिल्टर्सची दर्जेदार उत्पादने.
- ❖ सर्व स्प्रिंकलर फिटींग्सचे उत्पादक.



सुक्ष्मसिंचनातून  
समृद्धीकडे

## SPRINKLER FITTINGS

### M-TYPE COUPLERS



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	HDPE	GRADE-180M50 GAIL INDIA	Used to connect HDPE Pipe.
		C Clamp/Latch thickness 3 to3.5 mm	
		Pressure - 2.5kg/3.2kg./cm <sup>2</sup>	
		Colour - Black	

### C-TYPE COUPLERS



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	HDPE	GRADE-180M50 GAIL INDIA	Used to connect HDPE Pipe.
		C Clamp/Latch thickness 3 to3.5 mm	
		Pressure - 2.5kg/3.2kg./cm <sup>2</sup>	
		Colour - Black	

### TEE



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	HDPE	GRADE-180M50 GAIL INDIA	Used to make sublines in mainline.
		C Clamp/Latch thickness 3 to3.5 mm	
		Pressure - 2.5kg/3.2kg./cm <sup>2</sup>	
		Colour - Black	

### BEND



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	HDPE	GRADE-180M50 GAIL INDIA	Used to Divert the Pipe Line
		C Clamp/Latch thickness 3 to3.5 mm	
		Pressure - 2.5kg/3.2kg./cm <sup>2</sup>	
		Colour - Black	

## SPRINKLER FITTINGS

**ADAPTOR WITH FOOT BOTTOM**



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	HDPE	GRADE-180M50 GAIL INDIA	Used to hold the riser pipe & Sprinkle water around.
		C Clamp/Latch thickness 3 to 3.5 mm	
		Pressure - 2.5kg/3.2kg./cm <sup>2</sup>	
		Colour - Black	

**END CAP**



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	HDPE	GRADE-180M50 GAIL INDIA	Used to stop the Pipeline connection
		C Clamp/Latch thickness 3 to 3.5 mm	
		Pressure - 2.5kg/3.2kg./cm <sup>2</sup>	
		Colour - Black	

**PCN**



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	HDPE	GRADE-180M50 GAIL INDIA	Used as a Pump connector.
	HDPE	C Clamp/Latch thickness 3 to 3.5 mm	
		Pressure - 2.5kg/3.2kg./cm <sup>2</sup>	
		Colour - Black	

**RISER PIPE/ Nozzle**



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	GI	Length 1 Mtr	Used to hold the nozzle & Sprinkle water
3/4 inch	Brass /Plastic	Discharge 2/3kg/cm <sup>2</sup>	
		1800 to 2000 Lph	

## SPRINKLER FITTINGS

### J -TYPE COUPLERS (Fusion)



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	HDPE	GRADE-180M50 GAIL INDIA	Used to connect HDPE Pipe.
		C Clamp/Latch thickness 3 to3.5 mm	
		Pressure - 2.5kg/3.2kg./cm <sup>2</sup>	
		Colour - Black	

### J -TYPE COUPLERS (Butt Welding)



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	HDPE	GRADE-180M50 GAIL INDIA	Used to connect HDPE Pipe.
		C Clamp/Latch thickness 3 to3.5 mm	
		Pressure - 2.5kg/3.2kg./cm <sup>2</sup>	
		Colour - Black	

### J - TYPE TEE



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	HDPE	GRADE-180M50 GAIL INDIA	Used to make sublines in mainline.
		C Clamp/Latch thickness 3 to3.5 mm	
		Pressure - 2.5kg/3.2kg./cm <sup>2</sup>	
		Colour - Black	

### J - TYPE BEND



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	HDPE	GRADE-180M50 GAIL INDIA	Used to Divert the Pipe Line
		C Clamp/Latch thickness 3 to3.5 mm	
		Pressure - 2.5kg/3.2kg./cm <sup>2</sup>	
		Colour - Black	

## SPRINKLER FITTINGS

**J - TYPE ADAPTOR WITH FOOT BOTTOM**



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	HDPE	GRADE-180M50 GAIL INDIA	Used to hold the riser pipe & Sprinkle water around.
		C Clamp/Latch thickness 3 to 3.5 mm	
		Pressure - 2.5kg/3.2kg./cm <sup>2</sup>	
		Colour - Black	

**J - TYPE END CAP**



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	HDPE	GRADE-180M50 GAIL INDIA	Used to stop the Pipeline connection
		C Clamp/Latch thickness 3 to 3.5 mm	
		Pressure - 2.5kg/3.2kg./cm <sup>2</sup>	
		Colour - Black	

**J - TYPE PCN**



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	HDPE	GRADE-180M50 GAIL INDIA	Used as a Pump connector.
		C Clamp/Latch thickness 3 to 3.5 mm	
		Pressure - 2.5kg/3.2kg./cm <sup>2</sup>	
		Colour - Black	

**RISER PIPE/ Nozzle**



SIZES	MATERIAL	SPECIFICATION	APPLICATION
63/75/90/110	GI	Length 1 Mtr	Used to hold the nozzle & Sprinkle water
3/4 inch	Brass /Plastic	Discharge 2/3kg/cm <sup>2</sup>	
		1800 to 2000 Lph	

*Micro Irrigation*



*to Prosperity...!*

## LAXMI SPRINKLER SYSTEMS FEATURES :

### Application :

- Laxmi Sprinkler Irrigation Systems Sprinkles water as a Rainfall & is suitable for almost all field crops like vegetables, wheat, groundnut, cotton etc.

### Advantages :

- Maximum water saving.
- Uniform distribution of water.
- Easy to Install.
- Suitable for slopping Land.

### Features :

- Sprinkler fittings are manufactured in virgin quality.
- No effect of UV rays.
- Impact sprinkler in circle.



**LAXMI**<sup>®</sup>  
**DRIP SYSTEMS**

FACT. : M - 8, M.I.D.C. JALGAON - 425003 (M.S.)  
TEL.: 0257- 2270226, 2210966, CELL : 9158882310, 9130000814  
E-mail : [info@laxmirubberdrip.com](mailto:info@laxmirubberdrip.com)

**Visit us : [www.laxmirubberdrip.com](http://www.laxmirubberdrip.com)**